TILE ROOFING HOOK GUIDE





Curved or Flat



W-Tile



S-Tile



ALL TILE

CURVED TILE


FLAT TILE

17589* 17598* 17702* 17510* 17522* 17572* 17576* 17708* 17542*

*View part numbers on quickbolt.com for full selection of quantity variations and screw options

Roof Category	QuickBOLT Hook Base Part#	Adjustability	<u>A</u> Mounting Screw Slot	<u>B</u> Rail Slot Size	<u>C</u> Length of Hook	<u>D</u> Bottom End to Top End Height	<u>E</u> Hook Thickness	F1 Min Tile Clearance Height	F2 Clearance Height at Max Adjustability
All Tile	17589	Adjustable	9mm x 18mm	10mm x <i>7</i> 1 mm	179.5mm	190.3mm - 198.5mm	6mm	34mm	42mm
All Tile	17598	Adjustable	9mm x 37mm	10.2mm x 46mm	175.5mm	1 <i>77</i> mm	5mm	45mm	68.5mm
All Tile	17702	Adjustable	9mm x 18mm	10.2mm x 46mm	201.9mm	170.3mm - 178.5mm	5mm	34mm	42mm
Curved Tile	17510	Fixed	7.5mm x 37mm	10mm x 46mm	151 mm	165mm	5mm	40mm	40mm
Curved Tile	17522	Adjustable	7.5mm x 37mm	10mm x 48mm	151 mm	192mm - 214mm	5mm	69mm	91 mm
Curved Tile	17572	Adjustable	9mm x 18mm	10mm x 46mm	179.5mm	165.3mm - 173.5mm	6mm	42mm	50mm
Curved Tile	17576	Adjustable	9mm x 37mm	10mm x 46mm	180.5mm	178mm	6mm	42mm	50mm
Curved Tile	17708	Fixed	9mm x 37mm	10.2mm x 46mm	156mm	165mm	5mm	45mm	45mm
Flat Tile	17542	Fixed	9mm	10mm x 46mm	286mm	158mm	5mm	38mm	38mm


Let- ter	Description				
Α	Mounting Screw Slot				
В	Rail Slot Size				
С	Length of Roof Hook				
D	Bottom End to Top End				
E	Thickness				
F1-F2	Tile Clearance Range				



NEED TILE FLASHING?







#15991 Galva Flashing For Flat Tile Hooks

