

Quick Catalog

ISSUE 1

Explore QuickBOLT's solutions for rooftop solar mounting, conduit support and roof patching. QuickBOLT's mounts are the best in the industry and continue to improve the daily job of solar installation. This Quick Catalog is a cheat sheet to our products. For an extended list of all of our product variations, download the **Full Catalog** online.

SOLUTIONS FOR:

Asphalt, EPDM, TPO

Metal

All Tile

Flat Tile

Curved Tile

Stone Coated Steel

ROOF TYPE		MOUNT	PART #	TEST RESULT AVERAGES	CERTIFICATIONS
Asphalt, EPDM& TPO					
		QB2 with 3" Microflashing®	Silver: 17662; Black: 17862;	• 1,418 lb Uplift • 475 lb Lateral • 58 lb Bend	• Miami-Dade Approval • TAS 100(A)-95 • ASTM E331 • ASTM E2140 • ASTM D7147 • UL2703 Recognized Component
		QB2 with 4" Microflashing®	Silver: 17663; Black: 17863		
		QB2 with 3" Microflashing®	Black Split-Top: 17962	• 752 lb Uplift • 438 lb Lateral	• Miami-Dade Approval • TAS 100(A)-95 • ASTM E331 • ASTM E2140 • UL2703 Recognized Component
		QB2 with 4" Microflashing®	Black Split-Top: 17963		
		Butyl Bottom Deck Mount	Silver: 16319	• 1,310 lb Uplift • 460 lb Lateral • 1,073 lb Bend	• Miami-Dade Approval • TAS 100(A)-95 • ASTM D7147 • UL2703 Recognized Component
			Black: 16320		
Asphalt Shingle Only					
		Conduit Puck™ Kit	16323	• N/A	• TAS 100(A)-95
		Conduit Puck™	16321		
		QuickPATCH™	17782	• N/A	• N/A
Metal					
		QB RibRider®	17766	• 1,510 lb Uplift • 760 lb Lateral • 410 lb Lateral	• UL2703 Recognized Component • ASTM D7147
		The Throne	17747	• ,103 lb Uplift • 790 lb Lateral	• UL2703 Recognized Component

All Tile					
		Height Adjustable All Tile Roof Hook for Side Mount Rails	17587	• 2,091 lb Uplift • 487 lb Lateral • 395 lb Compression	• UL2703 Recognized Component
		Height Adjustable All Tile Roof Hook for Side Mount Rails	17598	• 2,434 lb Uplift • 306 lb Compression	• UL2703 Recognized Component
		Bracket for Tile Hooks	17734	• N/A	• N/A
Flat Tile					
		Flat Tile Roof Hook for Side Mount Rails	17542	• 203 lb Uplift • 141 lb Compression	• UL2703 Recognized Component
Curved / Spanish Tile					
		Non-Adjustable Hook for Side Mount Rails	17510	• 1,336 lb Uplift • 230 lb Compression	• UL2703 Recognized Component • ASTM D7147
Stone Coated Steel					
		Height Adj. 18mm for Side Mount Rails	17612	• 816 lb Uplift • 243 lb Lateral • 303 lb Compression	• Miami-Dade Approval • ASTM D7147 • UL2703 Recognized Component
		Non-Adjustable Hook for Side Mount Rails - Short	17624	• 1,617 lb Uplift • 152 lb Compression	• UL2703 Recognized Component
		Non-Adjustable No-Batten Hook for Side Mount Rails	17630	• 1,243 lb Uplift	• UL2703 Recognized Component
		Non-Adjustable Straight No-Batten Hook for Side Mount Rails	17752	• 1,689 lb Uplift • 3,109 lb Lateral	• UL2703 Recognized Component
		All Stone Coated Steel Hook with Wide Base, 12.5mm Height Adjust	17640	• 818 lb Uplift • 1,622 lb Compression	• UL2703 Recognized Component

If you have any questions about solar mounts or would like to discuss your project, QUICKBOLT is here to help. Our team is ready to consult with you and recommend the best mounts for your specific installation needs. Please reach out to your local QUICKBOLT [sales consultant](#) with any questions.

Expert Advice Available Monday - Friday, 7am - 5pm PST | (844) 671-6045